

#5 11-20-01

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of

NEVILL et al.

Serial No. 09/887,522

Filed: June 25, 2001

For: HARDWARE INSTRUCTION TRANSLATION WITHIN A
PROCESSOR PIPELINE



Atty. Ref.: 550-241

Group:

Examiner:

* * * * *

October 11, 2001

Assistant Commissioner for Patents
Washington, DC 20231

SUBMISSION OF PRIORITY DOCUMENTS

Sir:

It is respectfully requested that this application be given the benefit of the foreign filing date under the provisions of 35 U.S.C. §119 of the following, a certified copy of which is submitted herewith:

Application No.

0024396.4

Country of Origin

UNITED KINGDOM

Filed

5 October 2000

Respectfully submitted,

NIXON & VANDERHYE P.C.

By:

Stanley C. Spooner

Reg. No. 27,393

SCS:kmm

1100 North Glebe Road, 8th Floor

Arlington, VA 22201-4714

Telephone: (703) 816-4000

Facsimile: (703) 816-4100





INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ




I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated 26 July 2001

**CERTIFIED COPY OF
PRIORITY DOCUMENT**



Request for a grant of a patent

(See the notes on the back of this form you can also get an explanatory leaflet from the Patent Office to help you fill in this form)

P009828GB

1. Your reference

05 OCT 2000

0024396.4

2. Patent application number
(The Patent Office will fill in this part)

3. Full name, address and postcode of the
or of each applicant
(underline all surnames)

ARM Limited
110 Fulbourn Road
Cherry Hinton
Cambridge
CB1 9NJ
United Kingdom

7498124002

Patents ADP number (if you know it)

If the applicant is a corporate body, give
the country/state of its incorporation

United Kingdom

4. Title of the invention

HARDWARE INSTRUCTION TRANSLATION
WITHIN A PROCESSOR PIPELINE

5. Name of your agent (if you have one)

D YOUNG & CO

"Address for service" in the United Kingdom
to which all correspondence should be sent
(including the postcode)

21 NEW FETTER LANE
LONDON
EC4A 1DA

59006

Patents ADP number (if you know it)

6. If you are declaring priority from
one or more earlier patent
applications, give the country and
date of filing of the or each of these
earlier applications and (if you know
it) the or each application number

1st

2nd

3rd

Country

Priority application
number
(if you know it)

Date of filing
(day/month/year)

7. If this application is divided or otherwise
derived from an earlier UK application,
give the number and filing date of the
earlier application

Number of earlier
application

Date of filing
(day/month/year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:
a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See note (d))

Yes

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form 0

Description 30

Claim(s) 5

Abstract 1

Drawing(s) 10

10. If you are also filing any of the following, state how many against each item

Priority Documents 0

Translation of Priority Documents 0

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 3

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77) 0

Any other documents (Please specify) 0

11.

I/We request the grant of a Patent on the basis of this application.

Signature *DY*

Date

D YOUNG & CO
Agents for the Applicants

5 Oct 2000

12. Name and daytime telephone number of person to contact in the United Kingdom

Nigel Robinson

023 80634816


Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 01645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheets should be attached to this form.
- If you answered "Yes" Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

**Statement of inventorship and
of right to grant of a patent**



The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

05 OCT 2000

2. Patent application number (if you know it)

0024396.4

3. Full name of the or of each applicant

ARM Limited

4. Title of the invention

Hardware Instruction Translation Within a
Processor Pipeline

5. State how the applicant(s) derived the right from the
inventor(s) to be granted a patent

By Virtue of Employment

6. How many, if any, additional Patents Forms 7/77 are
attached to this form? (see note (c))

7.

I/We believe that the person(s) named over the page
(and on any extra copies of this forms) is/are the
inventor(s) of the invention which the above patent
relates to.

Signature

Date



D YOUNG & CO
Agents for the Applicants

5 Oct 2000

8. Name and daytime telephone number of person
to contact in the United Kingdom

023 80634816

Nigel Robinson

Notes

a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.

b) Write answers in capital letters using black ink or you may type them.

c) If there are more than three inventor, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.

d) When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.

e) Once you have filled in the form you must remember to sign and date it.

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

| | |
|--------------------------------------|--|
| Surname | <u>NEVILL</u> |
| First Names | Edward Colles |
| Address | Holly House 16 High Street Hemingford Grey Huntingdon PE18 9DR United Kingdom |
| 6577 464002 | |
| Patents ADP number (if you know it): | |

| | |
|--------------------------------------|---|
| Surname | <u>ROSE</u> |
| First Names | Andrew Christopher |
| Address | 69 Fulbourn Road Cherry Hinton Cambridge CB1 9JL United Kingdom |
| 7606932001 | |
| Patents ADP number (if you know it): | |

| | |
|--------------------------------------|-------|
| Surname | _____ |
| First Names | _____ |
| Address | _____ |
| Patents ADP number (if you know it): | |

Reminder:
Have you signed the form?

HARDWARE INSTRUCTION TRANSLATION WITHIN A PROCESSOR PIPELINE

This invention relates to data processing systems. More particularly, this invention relates to data processing systems in which instruction translation from one instruction set to another instruction set occurs within a processor pipeline.

It is known to provide processing systems in which instruction translation from a first instruction set to a second instruction set takes place within the instruction pipeline. In these systems each instruction to be translated maps to a single native instruction. An example of such systems are the processors produced by ARM Limited that support both ARM and Thumb instruction codes.

It is also known to provide processing systems in which non-native instructions may be translated into native instruction sequences comprising multiple native instructions. An example of such a system is described in US-A-5,937,193. This system maps Java bytecodes to 32-bit ARM instructions. The translation takes place before the instructions are passed into the processor pipeline and utilises memory address remapping techniques. A Java bytecode is used to look up a sequence of ARM instructions in a memory that then emulate the action of the Java bytecode.

The system of US-A-5,937,193 has several associated disadvantages. Such a system is inefficient in the way it utilises memory and memory fetches. The ARM instruction sequences all occupy the same amount of memory space even if they could be arranged to occupy less. Multiple fetches of ARM instructions from memory are required upon the decoding of each Java bytecode which disadvantageously consumes power and disadvantageously impacts performance. The translated instruction sequences are fixed making it difficult to take account of what may be different starting system states when executing each Java bytecode that could result in different, or better optimised, instruction translations.

Examples of known systems for translation between instruction sets and other background information may be found in the following: US-A-5,805,895; US-A-3,955,180; US-A-5,970,242; US-A-5,619,665; US-A-5,826,089; US-A-5,925,123; US-A-5,875,336; US-A-5,937,193; US-A-5,953,520; US-A-6,021,469; US-A-5,568,646; US-A-5,758,115; IBM

Technical Disclosure Bulletin, March 1988, pp308-309, "System/370 Emulator Assist Processor For a Reduced Instruction Set Computer"; IBM Technical Disclosure Bulletin, July 1986, pp548-549, "Full Function Series/1 Instruction Set Emulator"; IBM Technical Disclosure Bulletin, March 1994, pp605-606, "Real-Time CISC Architecture HW Emulator On A RISC Processor"; IBM Technical Disclosure Bulletin, March 1998, p272, "Performance Improvement Using An EMULATION Control Block"; IBM Technical Disclosure Bulletin, January 1995, pp537-540, "Fast Instruction Decode For Code Emulation on Reduced Instruction Set Computer/Cycles Systems"; IBM Technical Disclosure Bulletin, February 1993, pp231-234, "High Performance Dual Architecture Processor"; IBM Technical Disclosure Bulletin, August 1989, pp40-43, "System/370 I/O Channel Program Channel Command Word Prefetch"; IBM Technical Disclosure Bulletin, June 1985, pp305-306, "Fully Microcode-Controlled Emulation Architecture"; IBM Technical Disclosure Bulletin, March 1972, pp3074-3076, "Op Code and Status Handling For Emulation"; IBM Technical Disclosure Bulletin, August 1982, pp954-956, "On-Chip Microcoding of a Microprocessor With Most Frequently Used Instructions of Large System and Primitives Suitable for Coding Remaining Instructions"; IBM Technical Disclosure Bulletin, April 1983, pp5576-5577, "Emulation Instruction"; the book ARM System Architecture by S Furber and the book Computer Architecture: A Quantitative Approach by Hennessy and Patterson.

20 Viewed from one aspect the present invention provides apparatus for processing data, said apparatus comprising:

a processor core operable to execute operations as specified by instructions of a first instruction set, said processor core having an instruction pipeline into which instructions to be executed are fetched from a memory and along which instructions progress; and

25 an instruction translator operable to translate instructions of a second instruction set into translator output signals corresponding to instructions of said first instruction set; wherein said instruction translator is within said instruction pipeline and translates instructions of said second instruction set that have been fetched into said instruction pipeline from said memory;

30 at least one instruction of said second instruction set specifies a multi-step operation that requires a plurality of operations that may be specified by instructions of said first instruction set in order to be performed by said processor core; and

said instruction translator is operable to generate a sequence of translator output signals to control said processor core to perform said multi-step operation.

The present invention provides the instruction translator within the instruction pipeline of the processor core itself downstream of the fetch stage. In this way, the non-native instructions (second instruction set instructions) may be stored within the memory system in the same way as native instructions (first instruction set instructions) thereby removing what would otherwise be a constraint on memory system usage. Furthermore, for each non-native instruction, a single memory fetch of a non-native instruction from the memory system takes place with generation of any multi-step sequence of native instruction operations occurring within the processor pipeline. This reduces the power consumed by memory fetches and improves performance. In addition, the instruction translator within the pipeline is able to issue a variable number of native instruction operations down the remainder of the pipeline to be executed in dependence upon the particular non-native instruction being decoded and in dependence upon any surrounding system state that may influence what native operations may efficiently perform the desired non-native operation.

It will be appreciated that the instruction translator could generate translator output signals that fully and completely represent native instructions from the first instruction set. Such an arrangement may allow the simple re-use of hardware logic that was designed to operate with those instructions of the first instruction set. However, it will be appreciated that the instruction translator may also generate translator output signals that are control signals that can produce the same effect as native instructions without directly corresponding to them or additionally provide further operations, such as extended operand field, that were not in themselves directly provided by instructions of the first instruction set.

Providing the instruction translator within the instruction pipeline enables a program counter value for the processor core to be used to fetch non-native instructions from the memory in a conventional manner as the translation into native instructions of non-native instructions takes place without reliance upon the memory organisation. Furthermore, the program counter value may be controlled so as to be advanced in accordance with the execution of non-native instructions without a dependence upon whether or not those non-native instructions translate into single step or multi-step operations of native instructions. Using the program counter value to track the execution of non-native instructions advantageously simplifies methods for dealing with interrupts, branches and other aspects of the system design.

Providing the instruction translator within the instruction pipeline, in a way which may be considered as providing a finite state machine, has the result that the instruction translator is more readily able to adjust the translated instruction operations to reflect the system state as well as the non-native instruction being translated. As a particularly preferred example of this, when the second instruction set specifies stack based processing and the processor core is one intended for register based processing, then it is possible to use a set of the registers to effectively cache stack operands in order to speed up processing. In this circumstance, the translated instruction sequences may vary depending upon whether or not a particular stack operand is cached within a register or has to be fetched.

In order to reduce the impact that the instruction translator may have upon the execution of native instructions, preferred embodiments are such that the instruction translator within the instruction pipeline is provided with a bypass path such that, when operating in a native instruction processing mode, native instructions can be processed without being influenced by the instruction translator.

It will be appreciated that the native instructions and the non-native instructions could take many different forms. However, the invention is particularly useful when the non-native instructions of the second instruction set are Java Virtual Machine instructions as the translation of these instructions into native instructions presents many of the problems and difficulties which the present invention is able to address.

Viewed from another aspect the present invention provides a method of processing data using a processor core having an instruction pipeline into which instructions to be executed are fetched from a memory and along which instructions progress, said processor core being operable to execute operations specified by instructions of a first instruction set, said method comprising the steps of:

fetching instructions into said instruction pipeline; and
translating fetched instructions of a second instruction set into translator output signals corresponding to instructions of said first instruction set using an instruction translator within said instruction pipeline; wherein

at least one instruction of said second instruction set specifies a multi-step operation that requires a plurality of operations that may be specified by instructions of said first instruction set in order to be performed by said processor core; and

said instruction translator is operable to generate a sequence of translator output signals to control said processor core to perform said multi-step operation.

The invention also provides a computer program product holding a computer program for controlling a computer in accordance with the above technique.

When fetching instructions to be translated within an instruction pipeline a problem arises when the instructions to be translated are variable length instructions. The fetch stage of an instruction pipeline has relatively predictable operation when fetching fixed length instructions. For example, if an instruction is executed on each instruction cycle, then the fetch stage may be arranged to fetch an instruction upon each instruction cycle in order to keep the instruction pipeline full. However, when the instructions being fetched are of a variable length, then there is a difficulty in identifying the boundaries between instructions. Accordingly, in memory systems that provide fixed length memory reads, a particular variable length instruction may span between memory reads requiring a second fetch to read the final portion of an instruction.

Viewed from another aspect the invention provides apparatus for processing data, said apparatus comprising:

a processor core operable to execute operations as specified by instructions of a first instruction set, said processor core having an instruction pipeline into which instructions to be executed are fetched from a memory and along which instructions progress; and

an instruction translator operable to translate instructions of a second instruction set into translator output signals corresponding to instructions of said first instruction set; wherein said instructions of said second instruction set are variable length instructions;

said instruction translator is within said instruction pipeline and translates instructions of said second instruction set that have been fetched into a fetch stage of said instruction pipeline from said memory; and

said fetch stage of said instruction pipeline includes an instruction buffer holding at least a current instruction word and a next instruction word fetched from said memory such that if a variable length instruction of said second instruction set starts within said current

instruction word and extends into said next instruction word, then said next instruction word is available within said pipeline for translation by said instruction translator without requiring a further fetch operation.

5 The invention provides a buffer within the fetch stage storing at least a current instruction word and a next instruction word. In this way, if a particular variable length instruction extends out of the current instruction word into the next instruction word, then that instruction word has already been fetched and so is available for immediate decoding and use. Any second, power inefficient fetch is also avoided. It will be appreciated that providing a
10 fetch stage in the pipeline that buffers a next instruction word as well as the current instruction word and supports variable length instructions makes the fetch stage operate in a more asynchronous manner relative to the rest of the stages within the instruction pipeline. This is counter to the normal operational trend within instruction pipelines for executing fixed length instructions in which the pipeline stages tend to operate in synchronism.

15 Embodiments of the invention that buffer instructions within the fetch stage are well suited to use within systems that also have the above described preferred features set out in relation to the first aspect of the invention.

20 Viewed from another aspect the invention provides a method of processing data using a processor core operable to execute operations as specified by instructions of a first instruction set, said processor core having an instruction pipeline into which instructions to be executed are fetched from a memory and along which instructions progress, said method comprising the steps of:

25 fetching instructions into said instruction pipeline; and
 translating fetched instructions of a second instruction set into translator output signals corresponding to instructions of said first instruction set using an instruction translator within said instruction pipeline; wherein

 said instructions of said second instruction set are variable length instructions;
30 said instruction translator is within said instruction pipeline and translates instructions of said second instruction set that have been fetched into a fetch stage of said instruction pipeline from said memory; and

 said fetch stage of said instruction pipeline includes an instruction buffer holding at least a current instruction word and a next instruction word fetched from said memory such

that if a variable length instruction of said second instruction set starts within said current instruction word and extends into said next instruction word, then said next instruction word is available within said pipeline for translation by said instruction translator without requiring a further fetch operation.

5

Embodiments of the invention will now be described, by way of example only, with reference to the accompanying drawings in which:

Figures 1 and 2 schematically represent example instruction pipeline arrangements;

10

Figure 3 illustrates in more detail a fetch stage arrangement;

Figure 4 schematically illustrates the reading of variable length non-native instructions from within buffered instruction words within the fetch stage;

15

Figure 5 schematically illustrates a data processing system for executing both processor core native instructions and instructions requiring translation;

Figure 6 schematically illustrates, for a sequence of example instructions and states the contents of the registers used for stack operand storage, the mapping states and the relationship between instructions requiring translation and native instructions;

20

Figure 7 schematically illustrates the execution of a non-native instruction as a sequence of native instructions;

25

Figure 8 is a flow diagram illustrating the way in which the instruction translator may operate in a manner that preserves interrupt latency for translated instructions;

Figure 9 schematically illustrates the translation of Java bytecodes into ARM opcodes using hardware and software techniques;

30

Figure 10 schematically illustrates the flow of control between a hardware based translator, a software based interpreter and software based scheduling;

Figures 11 and 12 illustrate another way of controlling scheduling operations using a timer based approach; and

Figure 13 is a signal diagram illustrating the signals controlling the operation of the circuit of Figure 12.

Figure 1 shows a first example instruction pipeline 30 of a type suitable for use in an ARM processor based system. The instruction pipeline 30 includes a fetch stage 32, a native instruction (ARM/Thumb instructions) decode stage 34, an execute stage 36, a memory access stage 38 and a write back stage 40. The execute stage 36, the memory access stage 38 and the write back stage 40 are substantially conventional. Downstream of the fetch stage 32, and upstream of the native instruction decode stage 34, there is provided an instruction translator stage 42. The instruction translator stage 42 is a finite state machine that translates Java bytecode instructions of a variable length into native ARM instructions. The instruction translator stage 42 is capable of multi-step operation whereby a single Java bytecode instruction may generate a sequence of ARM instructions that are fed along the remainder of the instruction pipeline 30 to perform the operation specified by the Java bytecode instruction. Simple Java bytecode instructions may required only a single ARM instruction to perform their operation, whereas more complicated Java bytecode instructions, or in circumstances where the surrounding system state so dictates, several ARM instructions may be needed to provide the operation specified by the Java bytecode instruction. This multi-step operation takes place downstream of the fetch stage 32 and accordingly power is not expended upon fetching multiple translated ARM instructions or Java bytecodes from a memory system. The Java bytecode instructions are stored within the memory system in a conventional manner such that additional constraints are not provided upon the memory system in order to support the Java bytecode translation operation.

30

As illustrated, the instruction translator stage 42 is provided with a bypass path. When not operating in an instruction translating mode, the instruction pipeline 30 may bypass the instruction translator stage 42 and operate in an essentially unaltered manner to provide decoding of native instructions.

In the instruction pipeline 30, the instruction translator stage 42 is illustrated as generating translator output signals that fully represent corresponding ARM instructions and are passed via a multiplexer to the native instruction decoder 34. The instruction translator 42 also generates some extra control signals that may be passed to the native instruction decoder 34. Bit space constraints within the native instruction encoding may impose limitations upon the range of operands that may be specified by native instructions. These limitations are not necessarily shared by the non-native instructions. Extra control signals are provided to pass additional instruction specifying signals derived from the non-native instructions that would not be possible to specify within native instructions stored within memory. As an example, a native instruction may only provide a relatively low number of bits for use as an immediate operand field within a native instruction, whereas the non-native instruction may allow an extended range and this can be exploited by using the extra control signals to pass the extended portion of the immediate operand to the native instruction decoder 34 outside of the translated native instruction that is also passed to the native instruction decoder 34.

Figure 2 illustrates a further instruction pipeline 44. In this example, the system is provided with two native instruction decoders 46, 48 as well as a non-native instruction decoder 50. The non-native instruction decoder 50 is constrained in the operations it can specify by the execute stage 52, the memory stage 54 and the write back stage 56 that are provided to support the native instructions. Accordingly, the non-native instruction decoder 50 must effectively translate the non-native instructions into native operations (which may be a single native operation or a sequence of native operations) and then supply appropriate control signals to the execute stage 52 to carry out these one or more native operations. It will be appreciated that in this example the non-native instruction decoder does not produce signals that form a native instruction, but rather provides control signals that specify native instruction (or extended native instruction) operations. The control signals generated may not match the control signals generated by the native instruction decoders 46, 48.

In operation, an instruction fetched by the fetch stage 58 is selectively supplied to one of the instruction decoders 46, 48 or 50 in dependence upon the particular processing mode using the illustrated demultiplexer.

Figure 3 schematically illustrates the fetch stage of an instruction pipeline in more detail. Fetching logic 60 fetches fixed length instruction words from a memory system and supplies these to an instruction word buffer 62. The instruction word buffer 62 is a swing buffer having two sides such that it may store both a current instruction word and a next instruction word. Whenever the current instruction word has been fully decoded and decoding has progressed onto the next instruction word, then the fetch logic 60 serves to replace the previous current instruction word with the next instruction word to be fetched from memory, i.e. each side of the swing buffer will increment by two in an interleaved fashion the instruction words that they successively store.

In the example illustrated, the maximum instruction length of a Java bytecode instruction is three bytes. Accordingly, three multiplexers are provided that enable any three neighbouring bytes within either side of the word buffer 62 to be selected and supplied to the instruction translator 64. The word buffer 62 and the instruction translator 64 are also provided with a bypass path 66 for use when native instructions are being fetched and decoded.

It will be seen that each instruction word is fetched from memory once and stored within the word buffer 62. A single instruction word may have multiple Java bytecodes read from it as the instruction translator 64 performs the translation of Java bytecodes into ARM instructions. Variable length translated sequences of native instructions may be generated without requiring multiple memory system reads and without consuming memory resource or imposing other constraints upon the memory system as the instruction translation operations are confined within the instruction pipeline.

A program counter value is associated with each Java bytecode currently being translated. This program counter value is passed along the stages of the pipeline such that each stage is able, if necessary, to use the information regarding the particular Java bytecode it is processing. The program counter value for a Java bytecode that translates into a sequence of a plurality of ARM instruction operations is not incremented until the final ARM instruction operation within that sequence starts to be executed. Keeping the program counter value in a manner that continues to directly point to the instruction within the memory that is being executed advantageously simplifies other aspects of the system, such as debugging and branch target calculation.

Figure 4 schematically illustrates the reading of variable length Java bytecode instructions from the instruction buffer 62. At the first stage a Java bytecode instruction having a length of one is read and decoded. The next stage is a Java bytecode instruction that is three bytes in length and spans between two adjacent instruction words that have been fetched from the memory. Both of these instruction words are present within the instruction buffer 62 and so instruction decoding and processing is not delayed by this spanning of a variable length instruction between instruction words fetched. Once the three Java bytecodes have been read from the instruction buffer 62, the refill of the earlier fetched of the instruction words may commence as subsequent processing will continue with decoding of Java bytecodes from the following instruction word which is already present.

The final stage illustrated in Figure 4 illustrates a second three bytecode instruction being read. This again spans between instruction words. If the preceding instruction word has not yet completed its refill, then reading of the instruction may be delayed by a pipeline stall until the appropriate instruction word has been stored into the instruction buffer 62. In some embodiments the timings may be such that the pipeline never stalls due to this type of behaviour. It will be appreciated that the particular example is a relatively infrequent occurrence as most Java bytecodes are shorter than the examples illustrated and accordingly two successive decodes that both span between instruction words is relatively uncommon. A valid signal may be associated with each of the instruction words within the instruction buffer 62 in a manner that is able to signal whether or not the instruction word has appropriately been refilled before a Java bytecode has been read from it.

Figure 5 shows a data processing system 102 including a processor core 104 and a register bank 106. An instruction translator 108 is provided within the instruction path to translate Java Virtual Machine instructions to native ARM instructions (or control signals corresponding thereto) that may then be supplied to the processor core 104. The instruction translator 108 may be bypassed when native ARM instructions are being fetched from the addressable memory. The addressable memory may be a memory system such as a cache memory with further off-chip RAM memory. Providing the instruction translator 108 downstream of the memory system, and particularly the cache memory, allows efficient use to be made of the storage capacity of the memory system since dense instructions that require

translation may be stored within the memory system and only expanded into native instructions immediately prior to being passed to the processor core 104.

The register bank 106 in this example contains sixteen general purpose 32-bit registers, of which four are allocated for use in storing stack operands, i.e. the set of registers for storing stack operands is registers R0, R1, R2 and R3.

The set of registers may be empty, partly filled with stack operands or completely filled with stack operands. The particular register that currently holds the top of stack operand may be any of the registers within the set of registers. It will thus be appreciated that the instruction translator may be in any one of seventeen different mapping states corresponding to one state when all of the registers are empty and four groups of four states each corresponding to a respective different number of stack operands being held within the set of registers and with a different register holding the top of stack operand. Table 1 illustrates the seventeen different states of the state mapping for the instruction translator 108. It will be appreciated that with a different number of registers allocated for stack operand storage, or as a result of constraints that a particular processor core may have in the way it can manipulate data values held within registers, the mapping states can very considerably depending upon the particular implementation and Table 1 is only given as an example of one particular implementation.

| | | | |
|-------------|-------------|-------------|-------------|
| STATE 00000 | | | |
| R0 = EMPTY | | | |
| R1 = EMPTY | | | |
| R2 = EMPTY | | | |
| R3 = EMPTY | | | |
| STATE 00100 | STATE 01000 | STATE 01100 | STATE 10000 |
| R0 = TOS | R0 = TOS | R0 = TOS | R0 = TOS |
| R1 = EMPTY | R1 = EMPTY | R1 = EMPTY | R1 = TOS-3 |
| R2 = EMPTY | R2 = EMPTY | R2 = TOS-2 | R2 = TOS-2 |
| R3 = EMPTY | R3 = TOS-1 | R3 = TOS-1 | R3 = TOS-1 |
| STATE 00101 | STATE 01001 | STATE 01101 | STATE 10001 |
| R0 = EMPTY | R0 = TOS-1 | R0 = TOS-1 | R0 = TOS-1 |
| R1 = TOS | R1 = TOS | R1 = TOS | R1 = TOS |
| R2 = EMPTY | R2 = EMPTY | R2 = EMPTY | R2 = TOS-3 |
| R3 = EMPTY | R3 = EMPTY | R3 = TOS-2 | R3 = TOS-2 |
| STATE 00110 | STATE 01010 | STATE 01110 | STATE 10010 |

| | | | | |
|----|-------------|-------------|-------------|-------------|
| | R0 = EMPTY | R0 = EMPTY | R0 = TOS-2 | R0 = TOS-2 |
| | R1 = EMPTY | R1 = TOS-1 | R1 = TOS-1 | R1 = TOS-1 |
| | R2 = TOS | R2 = TOS | R2 = TOS | R2 = TOS |
| | R3 = EMPTY | R3 = EMPTY | R3 = EMPTY | R3 = TOS-3 |
| 5 | STATE 00111 | STATE 01011 | STATE 01111 | STATE 10011 |
| | R0 = EMPTY | R0 = EMPTY | R0 = EMPTY | R0 = TOS-3 |
| | R1 = EMPTY | R1 = EMPTY | R1 = TOS-2 | R1 = TOS-2 |
| 10 | R2 = EMPTY | R2 = TOS-1 | R2 = TOS-1 | R2 = TOS-1 |
| | R3 = TOS | R3 = TOS | R3 = TOS | R3 = TOS |

TABLE 1

15 Within Table 1 it may be observed that the first three bits of the state value indicate the number of non-empty registers within the set of registers. The final two bits of the state value indicate the register number of the register holding the top of stack operand. In this way, the state value may be readily used to control the operation of a hardware translator or a software translator to take account of the currently occupancy of the set of registers and the

20 current position of the top of stack operand.

As illustrated in Figure 5 a stream of Java bytecodes J1, J2, J3 is fed to the instruction translator 108 from the addressable memory system. The instruction translator 108 then outputs a stream of ARM instructions (or equivalent control signals, possibly extended)

25 dependent upon the input Java bytecodes and the instantaneous mapping state of the instruction translator 8, as well as other variables. The example illustrated shows Java bytecode J1 being mapped to ARM instructions A¹1 and A¹2. Java bytecode J2 maps to ARM instructions A²1, A²2 and A²3. Finally, Java bytecode J3 maps to ARM instruction A³1. Each of the Java bytecodes may require one or more stack operands as inputs and may

30 produce one or more stack operands as an output. Given that the processor core 104 in this example is an ARM processor core having a load/store architecture whereby only data values held within registers may be manipulated, the instruction translator 108 is arranged to generate ARM instructions that, as necessary, fetch any required stack operands into the set of registers before they are manipulated or store to addressable memory any currently held stack

35 operands within the set of registers to make room for result stack operands that may be generated. It will be appreciated that each Java bytecode may be considered as having an associated "require full" value indicating the number of stack operands that must be present within the set of registers prior to its execution together with a "require empty" value

indicating the number of empty registers within the set of registers that must be available prior to execution of the ARM instructions representing the Java opcode.

Table 2 illustrates the relationship between initial mapping state values, require full values, final state values and associated ARM instructions. The initial state values and the final state values correspond to the mapping states illustrated in Table 1. The instruction translator 108 determines a require full value associated with the particular Java bytecode (opcode) it is translating. The instruction translator (108), in dependence upon the initial mapping state that it has, determines whether or not more stack operands need to be loaded into the set of registers prior to executing the Java bytecode. Table 1 shows the initial states together with tests applied to the require full value of the Java bytecode that are together applied to determine whether a stack operand needs to be loaded into the set of registers using an associated ARM instruction (an LDR instruction) as well as the final mapping state that will be adopted after such a stack cache load operation. In practice, if more than one stack operand needs to be loaded into the set of registers prior to execution of the Java bytecode, then multiple mapping state transitions will occur, each with an associated ARM instruction loading a stack operand into one of the registers of the set of registers. In different embodiments it may be possible to load multiple stack operands in a single state transition and accordingly make mapping state changes beyond those illustrated in Table 2.

| INITIAL STATE | REQUIRE FULL | FINAL STATE | ACTIONS |
|------------------|-----------------|----------------|------------------------|
| 00000 | >0 | 00100 | LDR R0, [Rstack, #-4]! |
| 00100 | >1 | 01000 | LDR R3, [Rstack, #-4]! |
| 01001 | >2 | 01101 | LDR R3, [Rstack, #-4]! |
| 01110 | >3 | 10010 | LDR R3, [Rstack, #-4]! |
| 01111 | >3 | 10011 | LDR R0, [Rstack, #-4]! |
| 01100 | >3 | 10000 | LDR R1, [Rstack, #-4]! |
| 01101 | >3 | 10001 | LDR R2, [Rstack, #-4]! |
| 01010 | >2 | 01110 | LDR R0, [Rstack, #-4]! |
| 01011 | >2 | 01111 | LDR R1, [Rstack, #-4]! |
| 01000 | >2 | 01100 | LDR R2, [Rstack, #-4]! |
| 00110 | >1 | 01010 | LDR R1, [Rstack, #-4]! |
| 00111 | >1 | 01011 | LDR R2, [Rstack, #-4]! |
| 00101 | >1 | 01001 | LDR R0, [Rstack, #-4]! |

TABLE 2

As will be seen from Table 2, a new stack operand loaded into the set of registers storing stack operands will form a new top of stack operand and this will be loaded into a particular one of the registers within the set of registers depending upon the initial state.

Table 3 in a similar manner illustrates the relationship between initial state, require empty value, final state and an associated ARM instruction for emptying a register within the set of registers to move between the initial state and the final state if the require empty value of a particular Java bytecode indicates that it is necessary given the initial state before the Java bytecode is executed. The particular register values stored off to the addressable memory with an STR instruction will vary depending upon which of the registers is the current top of stack operand.

10

| INITIAL STATE | REQUIRE EMPTY | FINAL STATE | ACTIONS |
|------------------|------------------|----------------|----------------------|
| 00100 | >3 | 00000 | STR R0, [Rstack], #4 |
| 01001 | >2 | 00101 | STR R0, [Rstack], #4 |
| 15 01110 | >1 | 01010 | STR R0, [Rstack], #4 |
| 10011 | >0 | 01111 | STR R0, [Rstack], #4 |
| 10000 | >0 | 01100 | STR R1, [Rstack], #4 |
| 10001 | >0 | 01101 | STR R2, [Rstack], #4 |
| 10010 | >0 | 01110 | STR R3, [Rstack], #4 |
| 20 01111 | >1 | 01011 | STR R1, [Rstack], #4 |
| 01100 | >1 | 01000 | STR R2, [Rstack], #4 |
| 01101 | >1 | 01001 | STR R3, [Rstack], #4 |
| 01010 | >2 | 00110 | STR R1, [Rstack], #4 |
| 01011 | >2 | 00111 | STR R2, [Rstack], #4 |
| 25 01000 | >2 | 00100 | STR R3, [Rstack], #4 |
| 00110 | >3 | 00000 | STR R2, [Rstack], #4 |
| 00111 | >3 | 00000 | STR R3, [Rstack], #4 |
| 00101 | >3 | 00000 | STR R1, [Rstack], #4 |

30

TABLE 3

It will be appreciated that in the above described example system the require full and require empty conditions are mutually exclusive, that is to say only one of the require full or require empty conditions can be true at any given time for a particular Java bytecode which the instruction translator is attempting to translate. The instruction templates used by the instruction translator 108 together with the instructions it is chosen to support with the hardware instruction translator 108 are selected such that this mutually exclusive requirement may be met. If this requirement were not in place, then the situation could arise in which a particular Java bytecode required a number of input stack operands to be present within the set of registers that would not allow sufficient empty registers to be available after execution of the instruction representing the Java bytecode to allow the results of the execution to be held within the registers as required.

40

It will be appreciated that a given Java bytecode will have an overall nett stack action representing the balance between the number of stack operands consumed and the number of stack operands generated upon execution of that Java bytecode. Since the number of stack operands consumed is a requirement prior to execution and the number of stack operands generated is a requirement after execution, the require full and require empty values associated with each Java bytecode must be satisfied prior to execution of that bytecode even if the nett overall action would in itself be met. Table 4 illustrates the relationship between an initial state, an overall stack action, a final state and a change in register use and relative position of the top of stack operand (TOS). It may be that one or more of the state transitions illustrated in Table 2 or Table 3 need to be carried out prior to carrying out the state transitions illustrated in Table 4 in order to establish the preconditions for a given Java bytecode depending on the require full and require empty values of the Java bytecode.

| 15 | INITIAL STATE | STACK ACTION | FINAL STATE | ACTIONS |
|----|---------------|--------------|-------------|--|
| | 00000 | +1 | 00101 | R1 <- TOS |
| | 00000 | +2 | 01010 | R1 <- TOS-1, R2 <- TOS |
| | 00000 | +3 | 01111 | R1 <- TOS-2, R2 <- TOS-1, R3 <- TOS |
| 20 | 00000 | +4 | 10000 | R0 <- TOS, R1 <- TOS-3, R2 <- TOS-2, R3 <- TOS-1 |
| | 00100 | +1 | 01001 | R1 <- TOS |
| | 00100 | +2 | 01110 | R1 <- TOS-1, R2 <- TOS |
| | 00100 | +3 | 10011 | R1 <- TOS-2, R2 <- TOS-1, R3 <- TOS |
| 25 | 00100 | -1 | 00000 | R0 <- EMPTY |
| | 01001 | +1 | 01110 | R2 <- TOS |
| | 01001 | +2 | 10011 | R2 <- TOS-1, R3 <- TOS |
| | 01001 | -1 | 00100 | R1 <- EMPTY |
| 30 | 01001 | -2 | 00000 | R0 <- EMPTY, R1 <- EMPTY |
| | 01110 | +1 | 10011 | R3 <- TOS |
| | 01110 | -1 | 01001 | R2 <- EMPTY |
| | 01110 | -2 | 00100 | R1 <- EMPTY, R2 <- EMPTY |
| 35 | 01110 | -3 | 00000 | R0 <- EMPTY, R1 <- EMPTY, R2 <- EMPTY |
| | 10011 | -1 | 01110 | R3 <- EMPTY |
| | 10011 | -2 | 01001 | R2 <- EMPTY, R3 <- EMPTY |
| | 10011 | -3 | 00100 | R1 <- EMPTY, R2 <- EMPTY, R3 <- EMPTY |
| 40 | 10011 | -4 | 00000 | R0 <- EMPTY, R1 <- EMPTY, R2 <- EMPTY, R3 <- EMPTY |
| | 10000 | -1 | 01111 | R0 <- EMPTY |
| | 10000 | -2 | 01010 | R0 <- EMPTY, R3 <- EMPTY |
| | 10000 | -3 | 00101 | R0 <- EMPTY, R2 <- EMPTY, R3 <- EMPTY |
| 45 | 10000 | -4 | 00000 | R0 <- EMPTY, R1 <- EMPTY, R2 <- EMPTY, R3 <- EMPTY |

| | | | | | |
|----|-------|----|-------|--|----|
| | 10001 | -1 | 01100 | R1 <- EMPTY | |
| | 10001 | -2 | 01011 | R0 <- EMPTY, R1 <- EMPTY | |
| | 10001 | -3 | 00110 | R0 <- EMPTY, R1 <- EMPTY, R3 <- EMPTY | |
| 5 | 10001 | -4 | 00000 | R0 <- EMPTY, R1 <- EMPTY, R2 <- EMPTY, R3 <- EMPTY | |
| | 10010 | -1 | 01101 | R2 <- EMPTY | |
| | 10010 | -2 | 01000 | R1 <- EMPTY, R2 <- EMPTY | |
| 10 | 10010 | -3 | 00111 | R0 <- EMPTY, R1 <- EMPTY, R2 <- EMPTY | |
| | 10010 | -4 | 00000 | R0 <- EMPTY, R1 <- EMPTY, R2 <- EMPTY, R3 <- EMPTY | |
| | 01111 | +1 | 10000 | R0 <- TOS | |
| 15 | 01111 | -1 | 01010 | R3 <- EMPTY | |
| | 01111 | -2 | 00101 | R2 <- EMPTY, R3 <- EMPTY | |
| | 01111 | -3 | 00000 | R1 <- EMPTY, R2 <- EMPTY, R3 <- EMPTY | |
| | 01100 | +1 | 10001 | R1 <- TOS | |
| 20 | 01100 | -1 | 01011 | R0 <- EMPTY | |
| | 01100 | -2 | 00110 | R0 <- EMPTY, R3 <- EMPTY | |
| | 01100 | -3 | 00000 | R0 <- EMPTY, R2 <- EMPTY, R3 <- EMPTY | -- |
| | 01101 | +1 | 10010 | R2 <- TOS | |
| 25 | 01101 | -1 | 01000 | R1 <- EMPTY | |
| | 01101 | -2 | 00111 | R0 <- EMPTY, R1 <- EMPTY | |
| | 01101 | -3 | 00000 | R0 <- EMPTY, R1 <- EMPTY, R3 <- EMPTY | |
| | 01010 | +1 | 01111 | R3 <- TOS | |
| 30 | 01010 | +2 | 10000 | R3 <- TOS-1, R0 <- TOS | |
| | 01010 | -1 | 00101 | R2 <- EMPTY | |
| | 01010 | -2 | 00000 | R1 <- EMPTY, R2 <- EMPTY | |
| | 01011 | +1 | 01100 | R0 <- TOS | |
| 35 | 01011 | +2 | 10001 | R0 <- TOS-1, R1 <- TOS | |
| | 01011 | -1 | 00110 | R3 <- EMPTY | |
| | 01011 | -2 | 00000 | R2 <- EMPTY, R3 <- EMPTY | |
| | 01000 | +1 | 01101 | R1 <- TOS | |
| 40 | 01000 | +2 | 10010 | R1 <- TOS-1, R2 <- TOS | |
| | 01000 | -1 | 00111 | R0 <- EMPTY | |
| | 01000 | -2 | 00000 | R0 <- EMPTY, R3 <- EMPTY | |
| | 00110 | +1 | 01011 | R3 <- TOS | |
| 45 | 00110 | +2 | 01100 | R0 <- TOS, R3 <- TOS-1 | |
| | 00110 | +3 | 10001 | R1 <- TOS, R0 <- TOS-1, R3 <- TOS-2 | |
| | 00110 | -1 | 00000 | R2 <- EMPTY | |
| | 00111 | +1 | 01000 | R0 <- TOS | |
| 50 | 00111 | +2 | 01101 | R0 <- TOS-1, R1 <- TOS | |
| | 00111 | +3 | 10010 | R0 <- TOS-2, R1 <- TOS-1, R2 <- TOS | |
| | 00111 | -1 | 00000 | R3 <- EMPTY | |
| | 00101 | +1 | 01010 | R2 <- TOS | |
| 55 | 00101 | +2 | 01111 | R2 <- TOS-1, R3 <- TOS | |
| | 00101 | +3 | 10000 | R2 <- TOS-2, R3 <- TOS-1, R1 <- TOS | |
| | 00101 | -1 | 00000 | R1 <- EMPTY | |

TABLE 4

It will be appreciated that the relationships between states and conditions illustrated in Table 2, Table 3 and Table 4 could be combined into a single state transition table or state diagram, but they have been shown separately above to aid clarity.

5 The relationships between the different states, conditions, and nett actions may be used to define a hardware state machine (in the form of a finite state machine) for controlling this aspect of the operation of the instruction translator 108. Alternatively, these relationships could be modelled by software or a combination of hardware and software.

10 There follows below an example of a subset of the possible Java bytecodes that indicates for each Java bytecode of the subset the associated require full, require empty and stack action values for that bytecode which may be used in conjunction with Tables 2, 3 and 4.

```

15  --- iconst_0
    Operation:      Push int constant

    Stack:          ... =>
                   ..., 0

20                      Require-Full = 0
                      Require-Empty = 1
                      Stack-Action = +1

25  --- iadd
    Operation:      Add int

30  Stack:          ..., value1, value2 =>
                   ..., result

                      Require-Full = 2
                      Require-Empty = 0
                      Stack-Action = -1

35  --- lload_0
    Operation:      Load long from local variable

40  Stack:          ... =>
                   ..., value.word1, value.word2

                      Require-Full = 0
                      Require-Empty = 2
                      Stack-Action = +2

45  --- lastore
    Operation:      Store into long array
50
```

```

Stack:      ..., arrayref, index, value.word1, value.word2 =>
...

5           Require-Full = 4
           Require-Empty = 0
           Stack-Action = -4

--- land

10          Operation      Boolean AND long

Stack:      ..., value1.word1, value1.word2, value2.word1,
value2.word2 =>
15          ..., result.word1, result.word2

           Require-Full = 4
           Require-Empty = 0
           Stack-Action = -2

20          --- iastore

           Operation:      Store into int array

25          Stack:        ..., arrayref, index, value =>
...

           Require-Full = 3
           Require-Empty = 0
           Stack-Action = -3

30          --- ineg

           Operation:      Negate int

35          Stack:        ..., value =>
... result

           Require-Full = 1
           Require-Empty = 0
           Stack-Action = 0

40

```

There also follows example instruction templates for each of the Java bytecode

45 instructions set out above. The instructions shown are the ARM instructions which implement the required behaviour of each of the Java bytecodes. The register field "TOS-3", "TOS-2", "TOS-1", "TOS", "TOS+1" and "TOS+2" may be replaced with the appropriate register specifier as read from Table 1 depending upon the mapping state currently adopted. The denotation "TOS+n" indicates the Nth register above the register currently storing the top

50 of stack operand starting from the register storing the top of stack operand and counting upwards in register value until reaching the end of the set of registers at which point a wrap is made to the first register within the set of registers.

```

iconst_0      MOV    tos+1, #0
lload_0       LDR    tos+2, [vars, #4]
              LDR    tos+1, [vars, #0]
5 iastore      LDR    Rtmp2, [tos-2, #4]
              LDR    Rtmp1, [tos-2, #0]
              CMP    tos-1, Rtmp2, LSR #5
              BLXCS  Rexc
              STR    tos, [Rtmp1, tos-1, LSL #2]
10 lastore     LDR    Rtmp2, [tos-3, #4]
              LDR    Rtmp1, [tos-3, #0]
              CMP    tos-2, Rtmp2, LSR #5
              BLXCS  Rexc
15            STR    tos-1, [Rtmp1, tos-2, LSL #3]!
              STR    tos, [Rtmp1, #4]
iadd          ADD    tos-1, tos-1, tos
20 ineg        RSB    tos, tos, #0
land          AND    tos-2, tos-2, tos
              AND    tos-3, tos-3, tos-1
25

```

An example execution sequence is illustrated below of a single Java bytecode
 executed by a hardware translation unit 108 in accordance with the techniques described
 above. The execution sequence is shown in terms of an initial state progressing through a
 sequence of states dependent upon the instructions being executed, generating a sequence of
 30 ARM instructions as a result of the actions being performed on each state transition, the
 whole having the effect of translating a Java bytecode to a sequence of ARM instructions.

```

Initial state: 00000
Instruction:    iadd (Require-Full=2, Require-Empty=0, Stack-Action=-
35 1)
Condition:     Require-Full>0
State Transition: 00000 >0 00100
ARM Instruction(s): LDR R0, [Rstack, #-4]!

40 Next state: 00100
Instruction:    iadd (Require-Full=2, Require-Empty=0, Stack-Action=-
1)
Condition:     Requite-Full>1
State Transition: 00100 >1 01000
45 ARM Instructions(s): LDR R3, [Rstack, #-4]!

Next state:    01000
Instruction:    iadd (Require-Full=2, Require-Empty=0, Stack-Action=-
1)
Condition:     Stack-Action=-1
50 State Transition: 01000 -1 00111
Instruction template:
      ADD    tos-1, tos-1, tos
ARM Instructions(s) (after substitution):

```

ADD R3, R3, R0

Next state: 00111

Figure 6 illustrates in a different way the execution of a number of further Java bytecode instructions. The top portion of Figure 6 illustrates the sequence of ARM instructions and changes of mapping states and register contents that occur upon execution of an iadd Java bytecode instruction. The initial mapping state is 00000 corresponding to all of the registers within the set of registers being empty. The first two ARM instructions generated serve to POP two stack operands into the registers storing stack operands with the top of stack "TOS" register being R0. The third ARM instruction actually performs the add operation and writes the result into register R3 (which now becomes the top of stack operand) whilst consuming the stack operand that was previously held within register R1, thus producing an overall stack action of -1.

Processing then proceeds to execution of two Java bytecodes each representing a long load of two stack operands. The require empty condition of 2 for the first Java bytecode is immediately met and accordingly two ARM LDR instructions may be issued and executed. The mapping state after execution of the first long load Java bytecode is 01101. In this state the set of registers contains only a single empty register. The next Java bytecode long load instruction has a require empty value of 2 that is not met and accordingly the first action required is a PUSH of a stack operand to the addressable memory using an ARM STR instruction. This frees up a register within the set of registers for use by a new stack operand which may then be loaded as part of the two following LDR instructions. As previously mentioned, the instruction translation may be achieved by hardware, software, or a combination of the two. Given below is a subsection of an example software interpreter generated in accordance with the above described techniques.

| | | | |
|-----------|------|------------------------|---------------|
| Interpret | LDRB | Rtmp, [Rjpc, #1]! | |
| | LDR | pc, [pc, Rtmp, lsl #2] | |
| | DCD | 0 | |
| | ... | | |
| | DCD | do_iconst_0 | ; Opcode 0x03 |
| | ... | | |
| | DCD | do_lload_0 | ; Opcode 0x1e |
| | ... | | |
| | DCD | do_iastore | ; Opcode 0x4f |
| | DCD | do_lastore | ; Opcode 0x50 |
| | ... | | |
| | DCD | do_iadd | ; Opcode 0x60 |
| | ... | | |

```

DCD    do_inneg          ; Opcode 0x74
...
DCD    do_land           ; Opcode 0x7f
...
5  do_iconst_0          MOV    R0, #0
STR    R0, [Rstack], #4
B      Interpret
LDMIA  Rvars, {R0, R1}
STMIA  Rstack!, {R0, R1}
B      Interpret
10 do_oload_0           LDMDB  Rstack!, {R0, R1, R2}
LDR    Rtmp2, [r0, #4]
LDR    Rtmp1, [r0, #0]
CMP    R1, Rtmp2, LSR #5
BCS    ArrayBoundException
STR    R2, [Rtmp1, R1, LSL #2]
B      Interpret
15 do_iastore           LDMDB  Rstack!, {R0, R1, R2, R3}
LDR    Rtmp2, [r0, #4]
LDR    Rtmp1, [r0, #0]
CMP    R1, Rtmp2, LSR #5
BCS    ArrayBoundException
STR    R2, [Rtmp1, R1, LSL #3]!
STR    R3, [Rtmp1, #4]
B      Interpret
20 do_iastore           LDMDB  Rstack!, {r0, r1}
ADD    r0, r0, r1
STR    r0, [Rstack], #4
B      Interpret
25 do_iadd              LDR    r0, [Rstack, #-4]!
RSB    tos, tos, #0
STR    r0, [Rstack], #4
B      Interpret
30 do_inneg             LDMDB  Rstack!, {r0, r1, r2, r3}
AND    r1, r1, r3
AND    r0, r0, r2
STMIA  Rstack!, {r0, r1}
B      Interpret
35 do_land              LDRB   Rtmp, [Rjpc, #1]!
LDR    pc, [pc, Rtmp, lsl #2]
DCD    0
...
DCD    State_00000_do_iconst_0 ; Opcode 0x03
...
45 DCD    State_00000_do_oload_0 ; Opcode 0x1e
...
DCD    State_00000_do_iastore ; Opcode 0x4f
DCD    State_00000_do_iastore ; Opcode 0x50
...
50 DCD    State_00000_do_iadd ; Opcode 0x60
...
DCD    State_00000_do_inneg ; Opcode 0x74
...
DCD    State_00000_do_land ; Opcode 0x7f
...
55 State_00000_do_iconst_0 MOV    R1, #0
B      State_00101_Interpret
LDMIA  Rvars, {R1, R2}
B      State_01010_Interpret
60 State_00000_do_oload_0 LDMDB  Rstack!, {R0, R1, R2}
State_00000_do_iastore

```

```

5      LDR      Rtmp2, [r0, #4]
      LDR      Rtmp1, [r0, #0]
      CMP      R1, Rtmp2, LSR #5
      BCS      ArrayBoundException
      STR      R2, [Rtmp1, R1, LSL #2]
      B        State_00000_Interpret
State_00000_do_lastore LDMDB   Rstack!, {R0, R1, R2, R3}
      LDR      Rtmp2, [r0, #4]
      LDR      Rtmp1, [r0, #0]
10     CMP      R1, Rtmp2, LSR #5
      BCS      ArrayBoundException
      STR      R2, [Rtmp1, R1, LSL #3]!
      STR      R3, [Rtmp1, #4]
      B        State_00000_Interpret
15     State_00000_do_iadd LDMDB   Rstack!, {R1, R2}
      ADD      r1, r1, r2
      B        State_00101_Interpret
State_00000_do_ineg   LDR      r1, [Rstack, #-4]!
      RSB      r1, r1, #0
20     B        State_00101_Interpret
State_00000_do_land   LDR      r0, [Rstack, #-4]!
      LDMDB   Rstack!, {r1, r2, r3}
      AND      r2, r2, r0
      AND      r1, r1, r3
25     B        State_01010_Interpret

State_00100_Interpret LDRB     Rtmp, [Rjpc, #1]!
      LDR      pc, [pc, Rtmp, lsl #2]
      DCD      0
30     ...
      DCD      State_00100_do_iconst_0 ; Opcode 0x03
      ...
      DCD      State_00100_do_lload_0 ; Opcode 0x1e
      ...
35     DCD      State_00100_do_iastore ; Opcode 0x4f
      DCD      State_00100_do_lastore ; Opcode 0x50
      ...
      DCD      State_00100_do_iadd ; Opcode 0x60
      ...
40     DCD      State_00100_do_ineg ; Opcode 0x74
      ...
      DCD      State_00100_do_land ; Opcode 0x7f
      ...
State_00100_do_iconst_0 MOV     R1, #0
45     B        State_01001_Interpret
State_00100_do_lload_0 LDMIA   Rvars, {r1, R2}
      B        State_01110_Interpret
State_00100_do_iastore LDMDB   Rstack!, {r2, r3}
      LDR      Rtmp2, [r2, #4]
50     LDR      Rtmp1, [r2, #0]
      CMP      R3, Rtmp2, LSR #5
      BCS      ArrayBoundException
      STR      R0, [Rtmp1, R3, lsl #2]
      B        State_00000_Interpret
55     State_00100_do_lastore LDMDB   Rstack!, {r1, r2, r3}
      LDR      Rtmp2, [r1, #4]
      LDR      Rtmp1, [r1, #0]
      CMP      r2, Rtmp2, LSR #5
      BCS      ArrayBoundException
60     STR      r3, [Rtmp1, r2, lsl #3]!
      STR      r0, [Rtmp1, #4]

```

```

State_00100_do_iadd      B      State_00000_Interpret
                          LDR      r3, [Rstack, #-4]!
                          ADD      r3, r3, r0
                          B      State_00111_Interpret
5  State_00100_do_ineg    RSB      r0, r0, #0
                          B      State_00100_Interpret
                          LDMDB    Rstack!, {r1, r2, r3}
State_00100_do_land      AND      r2, r2, r0
                          AND      r1, r1, r3
                          B      State_01010_Interpret
10 State_01000_Interpret  LDRB     Rtmp, [Rjpc, #1]!
                          LDR      pc, [pc, Rtmp, lsl #2]
                          DCD      0
15 ...                   DCD      State_01000_do_iconst_0 ; Opcode 0x03
                          DCD      State_01000_do_lload_0 ; Opcode 0x1e
20 ...                   DCD      State_01000_do_iastore ; Opcode 0x4f
                          DCD      State_01000_do_lastore ; Opcode 0x50
                          DCD      State_01000_do_iadd ; Opcode 0x60
25 ...                   DCD      State_01000_do_ineg ; Opcode 0x74
                          DCD      State_01000_do_land ; Opcode 0x7f
30 State_01000_do_iconst_0 MOV     R1, #0
                          B      State_01101_Interpret
State_01000_do_lload_0   LDMIA    Rvars, {r1, r2}
                          B      State_10010_Interpret
State_01000_do_iastore   LDR      r1, [Rstack, #-4]!
                          LDR      Rtmp2, [R3, #4]
                          LDR      Rtmp1, [R3, #0]
35 ...                   CMP      r0, Rtmp2, LSR #5
                          BCS      ArrayOutOfBoundsException
                          STR      r1, [Rtmp1, r0, lsl #2]
                          B      State_00000_Interpret
40 State_01000_do_lastore LDMDB    Rstack!, {r1, r2}
                          LDR      Rtmp2, {r3, #4}
                          LDR      Rtmp1, {R3, #0}
                          CMP      r0, Rtmp2, LSR #5
                          BCS      ArrayOutOfBoundsException
45 ...                   STR      r1, [Rtmp1, r0, lsl #3]!
                          STR      r2, [Rtmp1, #4]
                          B      State_00000_Interpret
State_01000_do_iadd      ADD      r3, r3, r0
                          B      State_00111_Interpret
50 State_01000_do_ineg    RSB      r0, r0, #0
                          B      State_01000_Interpret
State_01000_do_land      LDMDB    Rstack!, {r1, r2}
                          AND      R0, R0, R2
                          AND      R3, R3, R1
                          B      State_01000_Interpret
55 ...                   ...
State_01100_Interpret    ...
State_10000_Interpret    ...
State_00101_Interpret    ...
60 State_01001_Interpret ...
State_01101_Interpret    ...

```



```

State_10001_Interpret ...
State_00110_Interpret ...
State_01010_Interpret ...
State_01110_Interpret ...
5 State_10010_Interpret ...
State_00111_Interpret ...
State_01011_Interpret ...
State_01111_Interpret ...
10 State_10011_Interpret ...

```

Figure 7 illustrates a Java bytecode instruction “laload” which has the function of reading two words of data from within a data array specified by two words of data starting at the top of stack position. The two words read from the data array then replace the two words that specified their position and to form the topmost stack entries.

In order that the “laload” instruction has sufficient register space for the temporary storage of the stack operands being fetched from the array without overwriting the input stack operands that specify the array and position within the array of the data, the Java bytecode instruction is specified as having a require empty value of 2, i.e. two of the registers within the register bank dedicated to stack operand storage must be emptied prior to executing the ARM instructions emulating the “laload” instruction. If there are not two empty registers when this Java bytecode is encountered, then store operations (STRs) may be performed to PUSH stack operands currently held within the registers out to memory so as to make space for the temporary storage necessary and meet the require empty value for the instruction.

The instruction also has a require full value of 2 as the position of the data is specified by an array location and an index within that array as two separate stack operands. The drawing illustrates the first state as already meeting the require full and require empty conditions and having a mapping state of “01001”. The “laload” instruction is broken down into three ARM instructions. The first of these loads the array reference into a spare working register outside of the set of registers acting as a register cache of stack operands. The second instruction then uses this array reference in conjunction with an index value within the array to access a first array word that is written into one of the empty registers dedicated to stack operand storage.

It is significant to note that after the execution of the first two ARM instructions, the mapping state of the system is not changed and the top of stack pointer remains where it started with the registers specified as empty still being so specified.

The final instruction within the sequence of ARM instructions loads the second array word into the set of registers for storing stack operands. As this is the final instruction, if an interrupt does occur during it, then it will not be serviced until after the instruction completes and so it is safe to change the input state with this instruction by a change to the mapping state of the registers storing stack operands. In this example, the mapping state changes to "01011" which places the new top of stack pointer at the second array word and indicates that the input variables of the array reference and index value are now empty registers, i.e. marking the registers as empty is equivalent to removing the values they held from the stack.

It will be noted that whilst the overall stack action of the "laload" instruction has not changed the number of stack operands held within the registers, a mapping state swap has nevertheless occurred. The change of mapping state performed upon execution of the final operation is hardwired into the instruction translator as a function of the Java bytecode being translated and is indicated by the "swap" parameter shown as a characteristic of the "laload" instruction.

Whilst the example of this drawing is one specific instruction, it will be appreciated that the principles set out may be extended to many different Java bytecode instructions that are emulated as ARM instructions or other types of instruction.

Figure 8 is a flow diagram schematically illustrating the above technique. At step 10 a Java bytecode is fetched from memory. At step 12 the require full and require empty values for that Java bytecode are examined. If either of the require empty or require full conditions are not met, then respective PUSH and POP operations of stack operands (possibly multiple stack operands) may be performed with steps 14 and 16. It is will be noted that this particular system does not allow the require empty and require full conditions to be simultaneously unmet. Multiple passes through steps 14 and 16 may be required until the condition of step 12 is met.

At step 18, the first ARM instruction specified within the translation template for the Java bytecode concerned is selected. At step 20, a check is made as to whether or not the selected ARM instruction is the final instruction to be executed in the emulation of the Java bytecode fetched at step 10. If the ARM instruction being executed is the final instruction,

then step 21 serves to update the program counter value to point to the next Java bytecode in the sequence of instructions to be executed. It will be understood that if the ARM instruction is the final instruction, then it will complete its execution irrespective of whether or not an interrupt now occurs and accordingly it is safe to update the program counter value to the next
5 Java bytecode and restart execution from that point as the state of the system will have reached that matching normal, uninterrupted, full execution of the Java bytecode. If the test at step 20 indicates that the final bytecode has not been reached, then updating of the program counter value is bypassed.

10 Step 22 executes the current ARM instruction. At step 24 a test is made as to whether or not there are any more ARM instructions that require executing as part of the template. If there are more ARM instructions, then the next of these is selected at step 26 and processing is returned to step 20. If there are no more instructions, then processing proceeds to step 28 at which any mapping change/swap specified for the Java bytecode concerned is performed in
15 order to reflect the desired top of stack location and full/empty status of the various registers holding stack operands.

Figure 8 also schematically illustrates the points at which an interrupt if asserted is serviced and then processing restarted after an interrupt. An interrupt starts to be serviced
20 after the execution of an ARM instruction currently in progress at step 22 with whatever is the current program counter value being stored as a return point with the bytecode sequence. If the current ARM instruction executing is the final instruction within the template sequence, then step 21 will have just updated the program counter value and accordingly this will point to the next Java bytecode (or ARM instruction should an instruction set switch have just been
25 initiated). If the currently executing ARM instruction is anything other than the final instruction in the sequence, then the program counter value will still be the same as that indicated at the start of the execution of the Java bytecode concerned and accordingly when a return is made, the whole Java bytecode will be re-executed.

30 Figure 9 illustrates a Java bytecode translation unit 68 that receives a stream of Java bytecodes and outputs a translated stream of ARM instructions (or corresponding control signals) to control the action of a processor core. As described previously, the Java bytecode translator 68 translates simple Java bytecodes using instruction templates into ARM instructions or sequences of ARM instructions. When each Java bytecode has been executed, then a counter

value within scheduling control logic 70 is decremented. When this counter value reaches 0, then the Java bytecode translation unit 68 issues an ARM instruction branching to scheduling code that manages scheduling between threads or tasks as appropriate.

5 Whilst simple Java bytecodes are handled by the Java bytecode translation unit 68 itself providing high speed hardware based execution of these bytecodes, bytecodes requiring more complex processing operations are sent to a software interpreter provided in the form of a collection of interpretation routines (examples of a selection of such routines are given earlier in this description). More specifically, the Java bytecode translation unit 68 can determine that the
10 bytecode it has received is not one which is supported by hardware translation and accordingly a branch can be made to an address dependent upon that Java bytecode where a software routine for interpreting that bytecode is found or referenced. This mechanism can also be employed when the scheduling logic 70 indicates that a scheduling operation is needed to yield a branch to the scheduling code.

15 Figure 10 illustrates the operation of the embodiment of Figure 9 in more detail and the split of tasks between hardware and software. All Java bytecodes are received by the Java bytecode translation unit 68 and cause the counter to be decremented at step 72. At step 74 a check is made as to whether or not the counter value has reached 0. If the counter value has
20 reached 0 (counting down from either a predetermined value hardwired into the system or a value that may be user controlled/programmed), then a branch is made to scheduling code at step 76. Once the scheduling code has completed at step 76, control is returned to the hardware and processing proceeds to step 72, where the next Java bytecode is fetched and the counter again decremented. Since the counter reached 0, then it will now roll round to a new, non-zero value.
25 Alternatively, a new value may be forced into the counter as part of the exiting of the scheduling process at step 76.

 If the test at step 74 indicated that the counter did not equal 0, then step 78 fetches the Java bytecode. At step 80 a determination is made as to whether the fetched bytecode is a simple
30 bytecode that may be executed by hardware translation at step 82 or requires more complex processing and accordingly should be passed out for software interpretation at step 84. If processing is passed out to software interpretation, then once this has completed control is returned to the hardware where step 72 decrements the counter again to take account of the fetching of the next Java bytecode.

Figure 11 illustrates an alternative control arrangement. At the start of processing at step 86 an instruction signal (scheduling signal) is deasserted. At step 88, a fetched Java bytecode is examined to see if it is a simple bytecode for which hardware translation is supported. If hardware translation is not supported, then control is passed out to the interpreting software at step 90 which then executes a ARM instruction routine to interpret the Java bytecode. If the bytecode is a simple one for which hardware translation is supported, then processing proceeds to step 92 at which one or more ARM instructions are issued in sequence by the Java bytecode translation unit 68 acting as a form of multi-cycle finite state machine. Once the Java bytecode has been properly executed either at step 90 or at step 92, then processing proceeds to step 94 at which the instruction signal is asserted for a short period prior to being deasserted at step 86. The assertion of the instruction signal indicates to external circuitry that an appropriate safe point has been reached at which a timer based scheduling interrupt could take place without risking a loss of data integrity due to the partial execution of an interpreted or translated instruction.

Figure 12 illustrates example circuitry that may be used to respond to the instruction signal generated in Figure 11. A timer 96 periodically generates a timer signal after expiry of a given time period. This timer signal is stored within a latch 98 until it is cleared by a clear timer interrupt signal. The output of the latch 98 is logically combined by an AND gate 100 with the instruction signal asserted at step 94. When the latch is set and the instruction signal is asserted, then an interrupt is generated as the output of the AND gate 100 and is used to trigger an interrupt that performs scheduling operations using the interrupt processing mechanisms provided within the system for standard interrupt processing. Once the interrupt signal has been generated, this in turn triggers the production of a clear timer interrupt signal that clears the latch 98 until the next timer output pulse occurs.

Figure 13 is a signal diagram illustrating the operation of the circuit of Figure 12. The processor core clock signals occur at a regular frequency. The timer 96 generates timer signals at predetermined periods to indicate that, when safe, a scheduling operation should be initiated. The timer signals are latched. Instruction signals are generated at times spaced apart by intervals that depend upon how quickly a particular Java bytecode was executed. A simple Java bytecode may execute in a single processor core clock cycle, or more typically two or three, whereas a complex Java bytecode providing a high level management type function may take several hundred processor clock cycles before its execution is completed by the software interpreter. In

either case, a pending asserted latched timer signal is not acted upon to trigger a scheduling operation until the instruction signal issues indicating that it is safe for the scheduling operation to commence. The simultaneous occurrence of a latched timer signal and the instruction signal triggers the generation of an interrupt signal followed immediately thereafter by a clear signal that clears the latch 98.

5

CLAIMS

1. Apparatus for processing data, said apparatus comprising:

a processor core operable to execute operations as specified by instructions of a first instruction set, said processor core having an instruction pipeline into which instructions to be executed are fetched from a memory and along which instructions progress; and

an instruction translator operable to translate instructions of a second instruction set into translator output signals corresponding to instructions of said first instruction set; wherein

said instruction translator is within said instruction pipeline and translates instructions of said second instruction set that have been fetched into said instruction pipeline from said memory;

at least one instruction of said second instruction set specifies a multi-step operation that requires a plurality of operations that may be specified by instructions of said first instruction set in order to be performed by said processor core; and

said instruction translator is operable to generate a sequence of translator output signals to control said processor core to perform said multi-step operation.

2. Apparatus as claimed in claim 1, wherein said translator output signals include signals forming an instruction of said first instruction set.

3. Apparatus as claimed in any one of claims 1 and 2, wherein said translator output signals include control signals that control operation of said processor core and match control signals produced on decoding instructions of said first instruction set.

4. Apparatus as claimed in any one of claims 1, 2 and 3, wherein said translator output signals include control signals that control operation of said processor core and specify parameters not specified by control signals produced on decoding instructions of said first instruction set.

5. Apparatus as claimed in any one of the preceding claims, wherein said processor core fetches instructions from an instruction address within said memory specified by a program counter value held by said processor core.

6. Apparatus as claimed in claim 5, wherein, when an instruction of said second instruction set is executed, said program counter value is advanced by an amount that is independent of whether or not said instruction of said second instruction set specifies a multi-step operation.

5 7. Apparatus as claimed in any one of claims 5 and 6, wherein, when an instruction of said second instruction set is executed, said program counter value is advanced to specify a next instruction of said second instruction set to be executed.

10 8. Apparatus as claimed in any one of claims 5, 6 and 7, wherein said program counter value is saved if an interrupt occurs when executing instructions of said second instruction set so and is used to restart execution of said instructions of said second instruction set after said interrupt.

15 9. Apparatus as claimed in any one of the preceding claims, wherein instructions of said second instruction set specify operations to be executed upon stack operands held in a stack.

10. Apparatus as claimed in any one of the preceding claims, wherein said processor has a register bank containing a plurality of registers and instructions of said first instruction set execute operations upon register operands held in said registers.

20 11. Apparatus as claimed in claim 10, wherein a set of registers within said register bank hold stack operands from a top portion of said stack.

25 12. Apparatus as claimed in claims 9 and 11, wherein said instruction translator has a plurality of mapping states in which different registers within said set of registers hold respective stack operands from different positions within said stack, said instruction translator being operable to move between mapping states in dependence upon operations that add or remove stack operands held within said stack.

30 13. Apparatus as claimed in any one of the preceding claims, further comprising a bypass path within said instruction pipeline such that said instruction translator may be bypassed when instructions of said second instruction set are not being processed.

14. Apparatus as claimed in any one of the preceding claims, wherein said instructions of said second instruction set are Java Virtual Machine bytecodes.

15. A method of processing data using a processor core having an instruction pipeline into which instructions to be executed are fetched from a memory and along which instructions progress, said processor core being operable to execute operations specified by instructions of a first instruction set, said method comprising the steps of:

fetching instructions into said instruction pipeline; and

translating fetched instructions of a second instruction set into translator output signals corresponding to instructions of said first instruction set using an instruction translator within said instruction pipeline; wherein

at least one instruction of said second instruction set specifies a multi-step operation that requires a plurality of operations that may be specified by instructions of said first instruction set in order to be performed by said processor core; and

said instruction translator is operable to generate a sequence of translator output signals to control said processor core to perform said multi-step operation.

16. A computer program product holding a computer program for controlling a computer to perform the method of claim 13.

17. Apparatus for processing data, said apparatus comprising:

a processor core operable to execute operations as specified by instructions of a first instruction set, said processor core having an instruction pipeline into which instructions to be executed are fetched from a memory and along which instructions progress; and

an instruction translator operable to translate instructions of a second instruction set into translator output signals corresponding to instructions of said first instruction set; wherein said instructions of said second instruction set are variable length instructions;

said instruction translator is within said instruction pipeline and translates instructions of said second instruction set that have been fetched into a fetch stage of said instruction pipeline from said memory; and

said fetch stage of said instruction pipeline includes an instruction buffer holding at least a current instruction word and a next instruction word fetched from said memory such that if a variable length instruction of said second instruction set starts within said current instruction word and extends into said next instruction word, then said next instruction word

is available within said pipeline for translation by said instruction translator without requiring a further fetch operation.

18. Apparatus as claimed in claim 17, wherein said instruction buffer is a swing buffer.

19. Apparatus as claimed in any one of claims 17 and 18, wherein said fetch stage includes a plurality of multiplexers for selecting a variable length instruction from one or more of said current instruction word and said next instruction word.

20. Apparatus as claimed in any one of claims 17, 18 and 19, wherein said instructions of said second instruction set are Java Virtual Machine bytecodes.

21. Apparatus as claimed in any one of claims 17 to 20, further comprising a bypass path within said instruction pipeline such that said instruction translator may be bypassed when instructions of said second instruction set are not being processed.

22. Apparatus as claimed in any one of claims 17 to 21, wherein at least one instruction of said second instruction set specifies a multi-step operation that requires a plurality of operations that may be specified by instructions of said first instruction set in order to be performed by said processor core; and said instruction translator is operable to generate a sequence of translator output signals to control said processor core to perform said multi-step operation.

23. Apparatus as claimed in claim 22 and any one of claims 2 to 12.

24. A method of processing data using a processor core operable to execute operations as specified by instructions of a first instruction set, said processor core having an instruction pipeline into which instructions to be executed are fetched from a memory and along which instructions progress, said method comprising the steps of:

fetching instructions into said instruction pipeline; and
translating fetched instructions of a second instruction set into translator output signals corresponding to instructions of said first instruction set using an instruction translator within said instruction pipeline; wherein
said instructions of said second instruction set are variable length instructions;

said instruction translator is within said instruction pipeline and translates instructions of said second instruction set that have been fetched into a fetch stage of said instruction pipeline from said memory; and

said fetch stage of said instruction pipeline includes an instruction buffer holding at least a current instruction word and a next instruction word fetched from said memory such that if a variable length instruction of said second instruction set starts within said current instruction word and extends into said next instruction word, then said next instruction word is available within said pipeline for translation by said instruction translator without requiring a further fetch operation.

25. A computer program product holding a computer program for controlling a computer to perform the method of claim 24.

26. Apparatus for data processing substantially as hereinbefore described with reference to the accompanying drawings.

27. A method of data processing substantially as hereinbefore described with reference to the accompanying drawings.

28. A computer program product holding a computer program for controlling a computer to perform a method substantially as hereinbefore described with reference to the accompanying drawings.

ABSTRACT**HARDWARE INSTRUCTION TRANSLATION WITHIN A PROCESSOR PIPELINE**

5 A processing system has an instruction pipeline (30) and a processor core. An instruction translator (42) for translating non-native instructions into native instruction operations is provided within the instruction pipeline downstream of the fetch stage (32). The instruction translator is able to generate multiple step sequences of native instruction operations in a manner that allows variable length native instruction operations sequences to be generated to emulate non-native instructions. The fetch stage is provided with a word
10 buffer (62) that stores both a current instruction word and a next instruction word. Accordingly, variable length non-native instructions that span between instruction words read from the memory may be provided for immediate decode and multiple power consuming memory fetch avoided.

15

[Figure 3]




Fig. 1

Fig. 2






Fig. 3



3/10




Fig. 4



4/10

102




Fig. 5



Fig. 6

| Java Instruction | load (RF=2, RF>0) | | load (RF=2, RF>1) | | - load (SA=-1) | |
|--------------------|---------------------------|---------|---------------------------|---------------|----------------|--|
| ARM Instruction(s) | ↗ LDR R0, [R0, #4]! (POP) | | ↗ LDR R3, [R0, #4]! (POP) | | ADD R3, R3, R0 | |
| State | 0000 | 00100 | 01000 | 00111 | -- | |
| R0 | E | SOA TOS | SOA TOS | E | | |
| R1 | E | E | E | E | | |
| R2 | E | E | E | E | | |
| R3 | E | E | SOB TOS-1 | (SOA+SOB) TOS | | |

5/10

| Java Instruction | load (RF=0, RE=2) | | load (RF=0, RE>2) | | load (RF=0, RE=2) | |
|------------------|--|-----------------|---------------------------|-----------|--------------------------------------|--|
| ARM Instructions | ↗ LDR R1, [R0, #4] ↘ LDR R0, [R0, #0] | | ↗ STR R3, [R0, #4] (PUSH) | | LDR R3, [R0, #4] LDR R2, [R0, #0] | |
| State | 00111 | 01101 | 01001 | 10011 | | |
| R0 | E | SOB TOS-1 | SOB TOS-1 | SOB TOS-3 | | |
| R1 | E | SOB TOS | SOB TOS | SOB TOS-2 | | |
| R2 | E | E | E | SOB TOS-1 | | |
| R3 | (SOA+SOB) TOS | (SOA+SOB) TOS-2 | E | SOB TOS | | |



load
 $RF = 2$ $SA = 0$
 $RE = 2$ (swap)

01001

| | |
|-----------|-------|
| Array Ref | TOS-1 |
| Index | TOS |
| | E |
| | E |

LDR R12, [R0, #0]
 LDR R2, [R12, R1, LSL #3]!

01001

| | |
|----------------|-------|
| Array Ref | TOS-1 |
| Index | TOS |
| 1st Array Word | E |
| | E |

01011

| | |
|----------------|-------|
| Array Ref | E |
| Index | E |
| 1st Array Word | TOS-1 |
| 2nd Array Word | TOS |

LDR R3, [R12, #4]
 (state swap)

Fig. 7



7/10




Fig. 8






Fig. 9




Fig. 10



2

3



Hardware

9/10

Software




Fig. 11




Fig. 12



10/10




Fig. 13

09/887,522